

MetaGuard 205

Dry Wipe Overlaminate



Product Description

Metaguard 205 Overlaminate can be applied over printed Metamark digital media such as MD3, to create dry wipe panels with printed graphics. The product is suitable for use with Dry Wipe marker pens only. The clear coated film wipes clean with a dry cloth. MetaGuard 205 is suitable for overlaminating prints on flat surfaces, for indoor use only.

Material Handling

- Ensure that the material has reached room temperature and a relative humidity of 50% before use.

Overlaminating

- Suitable for use on Solvent and Eco Solvent inkjet prints on Metamark print media
- Allow the inks to cure before overlaminating, this is usually 24-48 hours
- This product is suitable for cold lamination using a laminator. Apply around 30°C on the top roller to prevent silvering of the adhesive.
- Not suitable for wet application.
- Refer to www.metamark.co.uk for application guidelines.

Use of product

- Test suitability of pens before use. We suggest testing the NOBO Quartet Dry Erase Pens or EXPO Dry Erase Fine Tip pens.
- Use soft non abrasive cloth to clean the surface.
- To remove any built up staining use warm soapy water and non abrasive cloth.

Face Film

Face film	Coated Polypropylene
Gauge	25 micron nominal

Adhesive

Type	Permanent clear acrylic
Application temperature	+10°C
Service temperature	-40°C to + 80°C

Release Liner

Print	Unprinted
Weight	90gsm

Finishes

Finish Available	MG-205	Clear Gloss
------------------	--------	-------------

Roll Presentation

Roll sizes	645mm x 45m 1295mm x 45m
Presentation	Laminate outwards, on a 76mm core.

Durability

Chemical Resistance	Resistant to ammonium hydroxide 10%, detergent, distilled water, gasoline and hydrochloric acid 10%
Shelf Life	2 years
External weathering	Indoor Use Only. This refers to the overlaminate and not the protection that it gives the printed image.
Regulations	REACH compliant

Warranty: Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Media will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark Digital Vinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited

○ Luneside • New Quay Road • Lancaster • LA1 5QP • Tel +44 (0)1524 387140 • Fax +44 (0)1524 387147

○ Metamark House • Octimum Business Park • Forsyth Road • Woking • GU21 5SF • Tel +44 (0)1483 571111 • Fax +44 (0)1483 570540

sales@metamark.co.uk

www.metamark.co.uk

standKOLOR®