

SAFETY

TOP 300XR

OUTSIDE APPLICATION



The safety film TOP300 XR pushes the limits of safety. This evolution of the TOP 300 is the first safety film certified bulletproof. It is the most durable safety film ever produced to date and guarantees a perfect security of your premises. The perfectly colorless security film TOP 300XR forms a membrane that holds the glass in one piece, preventing from breaking into pieces in case of explosion or vandalism.



Durability: from 12 to 15 years for vertical application in central Europe.



Use: Réflectiv window films are designed for use on any type of clear normal glass.



Maintenance after 30 days: with usual cleaning solutions (non-abrasive, without ammonia...). Cleaning products that may scratch the film should be avoided.



Storage: 2 years from delivery. This film should be kept away from excessive humidity and sun rays, at temperatures below 38°C.

In order to constantly improve our production we may change a product colour and manufacturing process without prior notice.

INFORMATION

MATERIAL:	Laminated polyester
ADHESIVE:	.Acrylic polymer 28 gr/m ²
LINER:	
THICKNESS:	330 microns
APPLICATION FACE:	Outside
TENSILE STRENGTH :	From -20 to 80°C
THERMAL RESISTANCE:	100%
APPLICATION T°:	
FIRE RATING :	B-S1, D0
CEBTP STANDARDS NF EN 1	063 : BR1 NS
STANDARDS:	EUROCLASSES
GUARANTEE:	5 years*
DIMENSION:	1,52 x 30 m*

* For glazing not exposed to the sun





TOP 300XR

•BR1 NS• CERTIFIED

Application Method

The glass surface to be glued on has to be free from dust, grease or other contaminants. Some specific materials such as polycarbonate can cause air bubble problems. Therefore, a compatibility test is recommended. For more precision we recommend to refer back to the application table.

Production and standards

In order to constantly improve our production we may change a product colour and manufacturing process without prior notice. Before applying our products we recommend that our users ensure that the film is suitable for the intended use and comply with current standards.

Application's notice



Aplication's video



